H3 Electrocardiograph

Display:

6.2" LCD touch screen (resolution:600 × 480)

3 × 4 and 6 × 2 display format, 12-lead waveforms display simultaneously; Intelligent brightness sensor for automatic screen brightness adjust





Recording and Data printing

- 80mm × 20m Roll paper or Z-fold paper
- Built-in thermal printer / Optional: external printer
- Recording format:
- Built-in printer: 3×4、3×4+1R
- External printer: 3×4、3×4+1R、3×4+3R、6×2、 $6 \times 2 + 1R$, 12×1 , $12 \times 1 + T$
- 10,000 ECG built-in records with binary image format
- Connectable with FTP server for patient data remote-control
- Connectable with PC-based ECG management software
- Unlimited USB data transfer

Recording Mode

- a) Default Print: in automatic mode, ECG waveform is printed.
- b) One-key manual print: By pressing "print" again, rhythm-lead report is printed manually after the default full information report;
- c) Extendable print: In case arrhythmia occurs, rhythm-lead report is automatically printed after the default full information report.

- 1/3 channel rhythm lead display
- Support real-time sampling and pre-sampling
- Support synchronous sampling and sequential sampling
- ECG review, 600 seconds waveforms review and print for any 12 leads within 10 seconds
- Automatic standby and timing on-off function
- Li-thium battery
- Scanner connectable
- Smart touch screen with slide and multi-finger operate function
- Smart name and fuzzy ID search function



